

# **Ultra®Series**

## **Vertical Pump Motors**

NEMA Premium Efficient 3-1000 HP













### Motor technology for tomorrows challenges.

## The Most Robust WPI VHS Motor In The Industry



#### **Custom Motors Built Fast**

Ultra Series TEFC and WPI electrical systems, fans, couplings, end shields, bearings, bearing caps, and flanges are shared across designs resulting in some of the fastest custom cycle times in the industry.




## 20% Average Higher Standard Thrust

GEIM high thrust vertical pump motors have, on average, 20% higher thrust and extended performance than any other similar product in the industry

As a result, motors in all deep well applications can be air-cooled with any bearing configuration.

## PATENTED GECHANNEL COOLING TECHNOLOGY

Cooloing design improvements on larger TEFC frames result in an amazing - 30°C Temperature reduction dramatically extending bearing and winding life.



### Engineered for reliability.


GEGARD™ Insulation offers added protection in severe applications.

Our Class H GEGARD2400 insulation system exceeds NEMA MG1-31 (tested to with stand corona inception voltage of 2499 volts peak @ 0.1 seconds) for motors operating on inverters.

M w all the the process of the proce

#### **Rotational Varnish Application**

Motor coils are rotationally varnished with a "Trickle Treat" process while an electric current is passed through the windings to ensure a penetrating, thorough and even coating. This proven process fills air gaps that could cause corona inception damage during operation.




#### **Strong Bond**

Resin penetrates deep into tightly packed coil wire creating a strong bond that guards against end-turn vibration.

### **High Protection**


Contaminants can't penetrate carefully and tightly packed stator coils bonded by deep resin penetration into the slots.



The harmonics from VFDs induce a voltage on the shaft. This voltage will discharge through the bearings if the voltage is not grounded. Insulating one bearing prevents a ground loop from developing. To divert shaft currents from bearings and driven equipment, we include insulation for the thrust bearings in ratings 100HP+ and AegisTM shaft grounding rings are optional on all ratings.







## **Complete Product Line**









Product Name	WPI Ultra™ VHS	XSD Ultra™ VSS NT	XSD Ultra® VHS	XSD Ultra® 841 VSS	
Enclosure/Shaft Type	WPI hollow shaft	TEFC solid shaft	TEFC hollow shaft	TEFC solid shaft	
Speed	1200, 1800, 3600	1800/3600	1800, 3600	1800, 3600	
Voltage (60Hz*) 230/-	460, 460 PWS, 575, 380-440	230/460, 460	230/460, 460 PWS	460	
Base/Face	P-Base	P-Base	P-Base	P-Base and C-Face	
Thrust	100, 175, 300% High	Normal	100, 175, 300% High	Inline and 100% High	
HP Range (Standard)	5 - 600	3 - 150	5 - 300	3 - 300	
HP Range (Custom)	5 - 1000	3 - 500	5 - 600	3 - 500	
Efficiency	NEMA Premium	NEMA Premium	NEMA Premium	NEMA Premium	
Warranty	3 Years	3 Years	3 Years	3 Years	
Natar *Alas dual FOLL- non					

Notes: \*Also dual 50Hz nameplated.

Standard VHS Scope	WPI Ultra	WPI Ultra+
HP	5-400	40-600
Speed	1200, 1800, 3600	1800
Thrust	100 or 175% HT	100, 175%, 300% HT
Voltage	230/460, 460 PWS	230/460, 460 PWS, 575
Space Heater	Yes	Yes
GEGARD 2400 Inverter Duty Insulation	Yes	Yes
Class H Insulation System	Yes	Yes
Winding Thermostats		Yes
Insulated Thrust Bearings		Yes
Shaft Grounding Ring on NDE		Yes
Aegis SGR Extended Warranty		Yes

#### . . Caring For Your Needs

. . We understand that the goals of your organization are demanding, and evolving. That is why we offer a comprehensive range of aftermarket services including replacement units, field service spares, service . . agreements, unit upgrades and technical support.



