



# Petroleum & Chemical

AC/DC Motors Up to 1750 HP

GEWOLONG  
[www.gemotorswolong.com](http://www.gemotorswolong.com)



GE INDUSTRIAL MOTORS  
a **WOLONG** company





Electric motors make  
an average **70%**  
of total power cost\*

**\$87k/hr**

Average cost of  
unplanned downtime  
for a typical industrial  
processing plant\*\*

#### Challenges

- Multiple suppliers, designs and specifications tying up resources.
- Frequent unplanned maintenance disrupting operations requiring replacement motors onsite.
- Older low efficient motors eating profits.

#### Our Solutions

- Frame agreements increase supply and specification efficiency freeing up resources.
- Less unplanned maintenance and downtime with more robust motor designs.
- +1% energy efficiency gains translate to less than a two year payback.


\* <http://energy.gov/eere/amo/downloads/optimizing-your-motor-driven-system>





\*\* <https://iac.university/technicalDocs/prodman.pdf> (Page 67)



## Meeting Heavy Industrial Application Requirements

GEIM offers comprehensive motor solutions for petroleum and chemical applications. Chemical products result from a complex combination of reaction, distillation, absorption, filtration, extraction, drying, and screening operations. To remain competitive, most chemical processes must be efficient, and so the design of many production operations is focused on controlling and reducing loss of resources. Our durable and efficient motors provide a reliable lifeline to critical production equipment. Strict adherence to industry and application specifications also help ensure less downtime.




Application	Type	Requirements
 Blowers	Cooling Ventilation	Starting restriction ASD Applied IEEE-841, API 541, 546, 547
 Heat Exchangers	Air Cooling	Belt load specifications IEEE-841, API 661
 Pumps	Booster Liquid Cooling Jockey Pipeline Seawater Lift Water Injection Transfer	Starting restrictions ASD applied Vertical thrust loads Low inrush IEEE-841, API 541, 546, 547
 Compressors	Centrifugal Axial Pipeline Reciprocating	Starting restrictions/ASD applied/Low inrush/Special shaft and load designs/Torque pulsation/High rotor inertia/ API 541, 546, 547, 618



### Consider Lifecycle Operating Costs First


The initial cost of an electric motor makes up 5% or less of the total cost of operation. So all aspects of the motor operation should be considered when purchasing motors.



Heat	Heat
Load	Vibration
Inverters	Misalignment
Contamination	Contamination
Voltage Issues	Lubrication Issues
	Electrical Discharge
	Stress, Load, Fatigue


### Innovative Patented Air-Cooling Technology

GE engineers found a better way to air cool bearings in larger frame vertical TEFC motors. The design improvements result in an amazing ~30°C temperature reduction helping to dramatically extend bearing and winding life.



### Low Vibration Means Long Life

Vibration is bad for motors and driven equipment. Motor bearings, in particular, begin to wear faster with high vibration levels. Beyond focusing on proper alignment, base, and voltage, users should also pay more attention to the design of the motor itself. In most cases, manufacturers are content to simply stay within the NEMA or IEEE standards because many engineers, of course, specify these limits.



**It is well documented that motors designed with low vibration have longer bearing life.**


Since bearing wear is one of the leading causes of motor failure, reducing its chances reduces your unplanned downtime. Our application engineers have been told by many users that their driven equipment tends to run smoother with low vibration motors. All of this leads to lower maintenance costs on the entire drive system.





### GEgard™ Insulation offers added protection in severe applications.


Our Class H GEGARD insulation system is designed to excel in variable frequency drive applications where lesser designs often short circuit and cause overcurrent trips.



Larger Thermal Margin = Longer Motor Life

### Guarding Against Bearing Failure

Common shaft currents create voltage spikes that reach bearings causing them to vibrate in operation. Over a short period, this vibration (fluting) will degrade bearings to the point of failure. We include bearing insulation for higher ratings and Aegis™ shaft grounding rings are optional on all ratings.





Rigid and recessed severe-duty shaft slinger provides bearing system protection.

Cast iron bearing cap with gasket retains lubricant and protects the interior of the motor and the bearing system from contaminants.


### Rotational Varnish Application

Motor coils are rotationally varnished with a "Trickle Treat" process while an electric current is passed through the windings to ensure a penetrating, thorough and even coating. This proven process fills air gaps that could cause corona inception damage during operation.



### Wire Bonding


Resin penetrates deep into tightly packed coil wire creating a strong bond that guards against end-turn vibration.



### Moisture Protection

Contaminants can't penetrate carefully and tightly packed stator coils bonded by deep resin penetration into the slots.

## Severe Duty NEMA IE3



### NEMA Premium Efficient

This versatile and robust design is ideal for a wide range of challenging industrial applications and environments.


#### MODELS

- XSD Ultra
- XSD Ultra 841

#### Technical Capabilities

0.75-300 HP, 900-3600 RPM  
230/460, 460, 575V / 60 Hz  
Alternate 50 Hz data on nameplate  
TEFC (IP55)  
Frame sizes: 143T-449T  
NEMA, UL, CSA, IEEE 45, 841, 112B, and GM 7E-TA  
Division 2 applications  
C-Face and high-torque  
Design "C" models available  
VFD ready with GEGARD Class H (XSD Ultra)  
Five Year Warranty

## Severe Duty IEC IE3



### Rugged and Reliable

Based on the XSD Ultra mechanical and electrical design for the global market. Ideal for extreme environments.


#### MODEL

- XSD Ultra 841 IEC

#### Technical Capabilities

0.55-220 kW, 750-3000 / 900-3600 RPM  
200, 400, 400/690, 690V / 50 Hz  
230/460, 460, 575, 690V / 60 Hz  
TEFC (IP55)  
Frame size: 90S-280H  
IEC, IEEE 841, IEEE 45, ATEX, and IEC Exn  
Zone II, ABS  
VFD ready with GEGARD Class H insulation  
Five Year Warranty

## Energy Saver XP NEMA



### Protects Systems in Hazardous Zones

This enclosure has been specially designed to contain any sparking for hazardous environments where volatile gases may be present.

#### MODEL

- Energy Saver XP
- Energy Saver

#### Technical Capabilities

1-300 HP, 900-3600 RPM  
230/460, 460, 575V / 60 Hz  
Alternate 50 Hz data on nameplate  
TEFC (IP55) and ODP  
Frame sizes: 143T-449T  
NEMA, UL, CSA, IEEE 112B  
Division 1,  
Class I - Groups C, D  
Class II - Groups F, G  
Class F (ES) insulation  
Five Year Warranty





## Heat Exchange NEMA IE3



### Stable, Reliable, Efficient

Specially rated and ideally suited for harsh outdoor heat exchange applications.

#### MODELS

- XSD Ultra 661

#### Technical Capabilities

0.75-300 HP, 900-3600 RPM  
460, 575V / 60 Hz  
TEFC (IP55)  
Frame sizes: 184T-449  
NEMA, UL, CSA, API 661,  
IEEE 841, 45, 112B and GM 7E-TA  
CE, ATEX Zone 2  
Division 2 application  
VFD ready with GEGARD  
Class H insulation  
Five Year Warranty

## Vertical Pump NEMA IE3



### Inverter-Duty and Efficient

Combines extra severe duty engineering with advanced thrust and cooling technologies.

#### MODELS

- Ultra Series Vertical
- Large Custom Vertical
- Vertical Fire Pump

#### Technical Capabilities

3-1000HP, 600-3600 RPM  
460, 575, 2300/4160 V  
60Hz or 50Hz  
WPI and TEFC Enclosures  
Hollow and Solid Shaft  
Normal, High, and Extra High Thrusts  
Frame Size: 182-5013  
API 610 12th Edition  
P-Base mountings  
VFD ready with GEGARD  
Class H insulation  
Three Year Warranty

## Medium Voltage NEMA



### Severe Duty, Long Lasting

Designed to operate in extreme Petrochemical, Power Generation, Mining and general process environments and applications.

#### MODEL

- Quantum LMV

#### Technical Capabilities

100-1750 HP  
900-3600 RPM / 60 Hz  
900-3000 RPM / 50 Hz  
460, 575, 2300/4000, 6600V  
TEFC  
Available in IEEE 841 config.  
Frame sizes: 440-7000  
NEMA, CSA, UL, IEEE 112B, AEx nA  
API 547 and 541, Division 2, Zone 2  
Class F insulation  
Three Year or Five Year Warranties (IEEE 841)



GE INDUSTRIAL MOTORS  
a WOLONG company

# Access has never been easier!

search  
**Google**  
Type keyword  
"gemotorswolong"

## ONLINE STORE

view product offerings,  
orders, and find a local  
distributor

START HERE

## Motor Catalog

View updated information about standard motors on your mobile device. It can also be viewed offline and printed.

## E-Commerce

Find a distributor.  
Download datapacks.  
Access support library.

## News

The latest developments,  
new product introductions  
and special industry events.

Follow us  
on LinkedIn

## Our News

Headlines

